

ARS
Dust Collectors

20,000 CFM

Bridge, Marine,
Water Tank
Applications

DC20

One of the smallest footprints in the industry and provides the air movement of a much larger collector. The compact Low drag-High air flow design puts the maximum vacuum into the containment area where you need it most.



Features

~

Hydraulic Auger

~

15' Deck

~

Long Life Filters

~

Diesel or Electric

Specifications are subject to change without notice. Information contained in this brochure is not intended to extend any warranty or representation, expressed or implied, regarding the products described herein.

ARS RECYCLING SYSTEMS, LLC

info@arsrecycling.com
arsrecycling.com



4000 McCartney Road
Lowellville, OH 44436

p +330 536 8210
f +330 536 8211

Specifications

~

Air Rate Per Unit
20,000 CFM @ 16"wg.

Cartridge Efficiency
99.9% @ 0.5 microns

Arrangement of Elements
Vertical

Cartridge Cleaning
Ram Injection Pulse

Number of Filters
30

Filter Media Area
5,400 sq. ft.

Air-to-Cloth Ratio
3.7 @ 20,000CFM

Ducting Connections
Rear: 2 @ 20" diameter

Fan
Class IV non-overloading / Type "C" spark resistant

Engine
110 hp Diesel

Fuel Tank
75 gallon

Auger Drive
Hydraulic

Deck Length
15'

Dimensions
19'L x 8'W x 12'H

Brakes
Electric

Options
Hydraulic Compressor w/ Air Drying System
75 hp Electric Motor
Gooseneck Trailer
Certified Lift Available