Abrasive Blasting,
Painting and Coating
Applications
Commercial and Industrial



Tandem Recycling System allows for unlimited placement configurations.

ARS PERFORMANCE AND DURABILITY IN EVERY SYSTEM





Features

~

Certified Lift ~

Stackable Recycling Skid

Stackable Vacuum Skid

Separate Air Drying Skid

Specifications are subject to change without notice. Information contained in this brochure is not intended to extend any warranty or representation, expressed or implied, regarding the products described herein.

ARS RECYCLING SYSTEMS, LLC

info@arsrecycling.com arsrecycling.com



ney Road p +330 536 8210

f +330 536 8211

Specifications

VACUUM

Blower: 6,200 CFM or 5,200 CFM Vacuum: 28" hg - high vacuum

Cyclone: Prefilter
Stainless Steel Final Filter

High Vac Baghouse: 12 bag pulsating system

Power Plant: 350 hp electric Emergency Stop System: 4 locations

CLASSIFICATION

,

MAGNETIC PARTICLE SEPARATOR
VIBRATORY SCREENER/FEEDER
AIR WASH SEPARATORS: Five (5) Stage
BUCKET ELEVATORS: Two (2) per unit
LOW VAC BAGHOUSE: 4 bag pulsating system
FAN: 5 hp, 1,200 CFM, powers low-vac baghouse
ROTARY SCREEN: Precleaner

BLASTING

٠.

SIX (6) AUTO FILLED BLAST POTS 175 PSI, CODE STAMPED & REGISTERED AUGER BIN LOADING SYSTEM FULLY AUTOMATED CONTROL SYSTEM

AIR DRYING

~

TWO OVERSIZED AIR-COOLED AFTERCOOLERS
TWO LARGE CAPACITY DELIQUESCENT SALT TANKS
TWO PARTICULATE FILTERS
3" NPT PIPING / 4" PIPING AVAILABLE

DIMENSIONS

~

RECYCLER TRAILER: 31'L X 8'W X 13'6"H VACUUM TRAILER: 31'L X 8'W X 13'6"H

RECYCLER SKID: 26'L X 8'6"W X 10'6"H VACUUM SKID: 20'L X 8'6"W X 10'6"H AIR DRYING SKID: 8'L X 4'8"W X 10'H