


ARS
Dust Collectors

60,000 CFM

Bridge, Marine,
Water Tank
Applications

DC60

A transverse mounted, dual wheel fan allows for an extremely powerful dust collector with a minimized footprint. The advanced inlet design slows down incoming air for superior dust drop out. Two extra inlets provide added versatility at the job site.





Features

~

Hydraulic Auger

~

Only 34' long

~

Long Life Filter Cartridges

~

Low Drag - High Air Flow Design

Specifications are subject to change without notice. Information contained in this brochure is not intended to extend any warranty or representation, expressed or implied, regarding the products described herein.

ARS RECYCLING SYSTEMS, LLC

info@arsrecycling.com
arsrecycling.com



4000 McCartney Road
Lowellville, OH 44436

p +330 536 8210
f +330 536 8211

Specifications

~

Air Rate Per Unit
60,000 CFM @ 13"wg.

Cartridge Efficiency
99.9% @ 0.5 microns

Arrangement of Elements
Vertical

Cartridge Cleaning
Ram Injection, Pulse Type

Number of Filters
108

Filter Media Area
16,200 sq. ft.

Air-to-Cloth Ratio
3.7:1

Ducting Connections
Side: 5 @ 20" diameter / Rear: 2 @ 20" diameter

Fan
Class IV non-overloading / Type "C" spark resistant

Engine
200 hp Diesel

Fuel Tank
120 gallon

Auger Drive
Hydraulic

Dimensions
34'L x 8'W x 12'3"H

Brakes
Electric

Options
Hydraulic Compressor w/ Air Drying System
200 hp Electric Motor
Electric Soft Start System
Gooseneck Trailer
Certified Lift Available